

For more information, view our website on ProWood Micro Pressure-Treated Lumber at <http://www.ufpi.com/product/pwmicro/index.htm>

ProWood[®]
MICRO

**Limited
Warranty**

IMPORTANT: This is your warranty certificate. Attach your invoice and proof of warranty.

ELIGIBILITY

Universal Forest Products Western Division, Inc. (the "Warrantor"), is pleased to extend a Warranty to you. This Warranty is valid for standard residential applications and may not be assigned or transferred by you. The applicable Warranty Period is indicated on the product label or end tag. If there is no other indication, a One-Year Limited Warranty applies.

WARRANTY PERIOD

LIFETIME LIMITED WARRANTY

Warrantor will replace any genuine treated product used in a residential application which becomes structurally unfit due solely to damage caused by fungal decay or termites.

FIFTEEN-YEAR LIMITED WARRANTY

Warrantor will replace any genuine treated product used in a residential application which becomes structurally unfit due solely to damage caused by fungal decay or termites within fifteen years from the date of purchase.

TEN-YEAR LIMITED WARRANTY

Warrantor will replace any genuine treated product used in a residential application which becomes structurally unfit due solely to damage caused by fungal decay or termites within ten years from the date of purchase.

ONE-YEAR LIMITED WARRANTY

Warrantor will replace any genuine treated product used in a residential application which becomes structurally unfit due solely to damage caused by fungal decay or termites within one year from the date of purchase.

WARRANTY DETAILS

This Warranty does not cover costs of installation, removal, or reinstallation, or for the natural characteristic of some wood to split, warp or twist, or damage caused by physical abuse, acts of God, acts of war, or other chemical or biological factors. Warrantor's sole obligation is limited to replacement of the treated product, and Warrantor shall have no further liability or obligation except as expressly stated herein. Warrantor expressly disclaims any liability for incidental or consequential damages. The Warranty does not apply to any of the following uses: foundation piles, poles, supports in pole-frame structures, swimming pool sidewalls, tree, vine or plant supports, use in commercial or industrial projects or any application involving immersion of the product in water.

Always follow the guidelines stated in the applicable Safe Handling Information Sheet/Section when working with or handling this product. Warrantor reserves the right to investigate any claim and to inspect the materials on which a claim is made. Warrantor is not responsible for any application of the ProWood product other than that specified as the appropriate usage on the product end tag (e.g. "Above Ground Use Only" or "Not For Structural Use").

For Western species of wood (described in the Western Wood Products Association Grading Rules), this Warranty is invalid unless all end cuts and bore holes are end coated during construction with a suitable wood preservative.

Some states do not allow limitations on how long an implied warranty lasts and/or do not allow the exclusion of incidental or consequential damages, so the limitations and exclusions set forth herein may not apply to you. This Warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

CLAIM PROCEDURE

To make a claim under this Warranty to receive replacement wood, the original owner must, within 90 days of actual or constructive notice of fungal or termite damage, do the following:

(1) Prepare a letter which includes the following:

- A list of the number of pieces and the size of each piece for which the claim is made.
- Proof of Purchase of the product, as shown on the original invoice.
- Proof of Warranty, such as the original end tag from the product, copy of the mark on the product, or other evidence.

(2) Mail the above information to:

Universal Forest Products Western Division, Inc.
Warranty Information
2801 East Beltline N.E.
Grand Rapids, MI 49525

WARRANTOR DOES NOT MAKE ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO OTHER WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION IN THE FACE HEREOF.

Do More With Every Project!



Safe Handling Information

ProWood Micro Pressure-Treated Wood

This wood has been preserved by pressure treatment with an EPA-registered pesticide containing copper and quaternary compounds to protect it from termite attack and decay. ProWood Micro preservatives penetrate deeply into and will remain in the wood for a long period of time. However, some preservative may migrate from the preserved wood into surrounding soil or water over time and may dislodge from the wood during construction or use upon contact with skin. The following precautions should be taken when handling the treated wood and in determining where to use or dispose of the treated wood.

HANDLING AND USE RECOMMENDATIONS

Do not burn preserved wood (see Disposal section). Avoid prolonged inhalation of sawdust. When sawing, sanding, or machining wood, wear a dust mask. When power-sawing and machining wood, wear goggles. Wear gloves when working with wood. All sawdust and construction debris should be cleaned up and disposed of after construction. After working with the wood and before eating, drinking, toileting, and use of tobacco products, wash exposed areas thoroughly. Wash work clothes separately from other household clothing before reuse. Preserved wood should not be used where it may come into direct or indirect contact with drinking water, except for uses involving incidental contact such as freshwater docks and bridges. Do not use preserved wood under circumstances where the preservative may become a component of food, animal feed, or beehives. Do not use preserved wood for mulch. Only preserved wood that is visibly clean and free of surface residue should be used for patios, decks, and walkways. Use hot-dip galvanized or other fasteners and hardware as required by building codes. Aluminum building products can be placed in direct contact with ProWood Micro treated wood products used for interior uses and above ground exterior applications such as decks, fencing, and landscaping projects. Examples of aluminum products include siding, roofing, gutters, door and window trim, flashing, nails, fasteners and other hardware connectors. Aluminum contact is not recommended when ProWood Micro treated wood products are immersed in water or are subject to frequent and prolonged wetting or other severe exposure conditions. In such cases, a moisture resistant protective barrier should be placed between the aluminum products and ProWood Micro treated wood. Mold growth may occur on building products, including untreated or treated wood. To remove mold from a treated wood surface, mild soap and water is typically used.

DISPOSAL RECOMMENDATIONS

ProWood Micro products which are no longer usable, such as cutoffs, broken boards, sawdust or treated wood material taken out of service, may be disposed of in landfills. Treated wood should not be burned in open fires or in stoves, fireplaces, or residential boilers.